

MDF KIT ACTIVATOR

01 DESCRIPTION

MDF KIT ACTIVATOR is an adhesive set which consists of high viscosity cyanoacrylate adhesive and activator.

02 PROPERTIES

High bonding strength
 Suitable for use on vertical surfaces as it will not drip or slump.
 It is particularly suited to bonding difficult substrates which have a porous or uneven nature since it increases bonding strength by preventing the adhesive to be absorbed by the surface.

03 APPLICATIONS

It is particularly used for fixing and repairing wooden parts.
 Suitable for MDF, wood, chip wood, rubber, most plastics, leather etc.
 Especially suitable for the applications where cure speed needs to be accelerated.

04 INSTRUCTIONS

Substrates need to be smooth and have a perfect connection area. Apply a drop on one of the substrates. Join substrates and press firmly for one minute. Application temperature is between +5°C and +40°C.

05 STORAGE AND SHELF LIFE

12 months in unopened packaging in a dry and cool storage place at temperatures between +5°C and +25°C.

06 PACKAGING

Product	Volume	Package
705	200 ml + 50 gr	24
705	400 ml + 100 gr	24
705	100 ml + 20 gr	12

07 SAFETY

- Cyanoacrylates should ideally be stored in original sealed containers until used.
- Avoid exposure to strong light and heat sources
- Cyanoacrylates can bond to skin within seconds
- Do not drip into skin or into eyes - can cause serious injury to your eyes.
- Will become hard in container if not closed properly!
- Activator is flammable. Do not throw into fire. Do not inhale.
- Activator box is pressured. Do not crush or drill.



08 TECHNICAL PROPERTIES

Basis	:Ethyl-2-cyanoacrylate
Appearance	:Clear, colourless
Application Temperature	:+5 °C to +30 °C
Density	:1,05 ± 0,01 g/cm ³
Flashpoint	:≥81 °C